

## QUICK TECH TT42

**Kind : CNC lathe**  
**Manufacturer : QUICK TECH**  
**Model : TT42**  
**Year : 2011**  
**Serial : 2935**  
**Stock : T14426**



### TECHNICAL DETAILS

- Number of axes	: 8
- Number of spindles	: 2
- Number of turrets	: 2
MAIN SPINDLE	
- Spindle nose	: A2-5
- Spindle power	: 7,5 [kW]
- Spindle speeds	: 6.000 [rpm]
- Max. bar diameter	: 42 [mm]
- Max. turning length	: 230 [mm]
- C axis indexing precision	: 0,001 [°]
COUNTER-SPINDLE	
- Spindle nose	: A2-5
- Spindle power	: 3,7 [kW]
- Spindle speeds	: 6.000 [rpm]
- Max. bar diameter	: 42 [mm]
- Max. turning length	: 100 [mm]
- C axis indexing precision	: 0,001 [°]
- Z stroke	: 360 [mm]
- X stroke	: 410 [mm]
TOOL BLOCK SYSTEM 1	
- Number of positions	: 16
- Number of motorized positions	: 6
- X/Z stroke	: 140 x 230 [mm]
- Y stroke	: 410 [mm]
- Tool type	: ER20

**Kind : CNC lathe**  
**Manufacturer : QUICK TECH**  
**Model : TT42**  
**Year : 2011**  
**Serial : 2935**  
**Stock : T14426**

- Live tools speed : 4.000 [rpm]  
- Live tools power : 1 [kW]

**TOOL BLOCK SYSTEM 2**

- Number of positions : 15  
- Number of motorized positions : 6  
- Y stroke : 410 [mm]  
- Tool type : ER 20  
- Live tools speed : 4.000 [rpm]  
- Live tools power : 1 [kW]

**POWER SUPPLY**

- Supply voltage : 380 [V]  
- Total installed power : 20 [kVA]

**WEIGHT & DIMENSIONS**

- Machine floor space : 3.465 x 1.654 [mm]  
- Machine height : 1.896 [mm]  
- Machine weight : 4.200 [kg]

**MACHINE HOURS**

- Number of hours under power : 10363 [h]  
- Number of working hours : 7359 [h]

**EQUIPMENT**

- CNC : Mitsubishi M700  
- Interface : Ethernet / RS232 / USB / PCMCIA  
- 3 colors status lamp  
- Coolant tank  
- Chips conveyor  
- Parts catcher  
- Parts conveying strip  
- Collet chuck : 2x BELLEGRANDI 48F