

TRAUB TNL 12/7

Kind : Swiss-type cnc lathe
Manufacturer : TRAUB
Model : TNL 12/7
Year : 2001
Serial : 390
Stock : 9403



TECHNICAL DETAILS

| | |
|---------------------------------|-----------------|
| - Number of axes | : 9 |
| - Number of spindles | : 2 |
| MAIN SPINDLE | |
| - Max. bar diameter | : 12.7 [mm] |
| - Max. machining length | : 130 [mm] |
| - Spindle speeds | : 12000 [rpm] |
| - Spindle power | : 2.5 [kW] |
| - C axis indexing precision | : 0.001 [°] |
| COUNTER-SPINDLE | |
| - Max. bar diameter | : 12.7 [mm] |
| - Spindle speeds | : 12000 [rpm] |
| - Spindle power | : 2.5 [kW] |
| - C axis indexing precision | : 0.001 [°] |
| - Number of turrets | : 2 |
| UPPER TURRET | |
| - Number of positions | : 6 |
| - Number of motorized positions | : 6 |
| - X stroke | : 35 [mm] |
| - Y stroke | : -9.5/+28 [mm] |
| - Z stroke | : 48 [mm] |
| LOWER TURRET | |
| - Number of positions | : 6 |
| - Number of motorized positions | : 6 |
| - X/Z stroke | : 35/79.5 [mm] |
| END ATTACHMENT | |

Kind : Swiss-type cnc lathe

Manufacturer : TRAUB

Model : TNL 12/7

Year : 2001

Serial : 390

Stock : 9403

- Number of positions : 4
- Number of motorized positions : 4
- Live tools speed : 10000 [rpm]
- X/Z stroke : 415/138.5 [mm]

SECONDARY OPERATION

- Number of positions : 4
- Number of motorized positions : 4
- Live tools speed : 10000 [rpm]

POWER SUPPLY

- Supply voltage : 400 [V]

EQUIPMENT

- CNC : Traub TX8i
- Rotating guide bush
- Coolant tank
- Bar loader : LNS TRYTON HYBRID